
Filter

Filter | BG5




105 Ø100 45 Image shows: 9.1154.00.350.0V

flow characteristic



symbol



technical data

- description: sinter filter centrifugal principle
 medium: compressed air, neutral gases
 supply pressure P1 min.: 1,5 bar

- supply pressure P1 max.: 16 bar
 temperature range: -10°C +60°C
 bowl: PC
 drain: HA3

- mounting: vertical
- filter element: 40 µm

accessories


Filter

type	part-number	description
DF.54 HA3	9.1154.00.350.0V	Filter G3/4 40µm with PC bowl and semi automatic drain
DF.54 M HA3	9.1154.00.352.0V	Filter G3/4 40µm with metal bowl and semi automatic drain
DF.54 HA3 B	9.1154.00.353.0V	Filter G3/4 40µm with PC bowl, bowl guard and semi automatic drain
DF.54 AM10	9.1154.00.400.0V	Filter G3/4 40µm with PC bowl and automatic drain
DF.54 M AM10	9.1154.00.402.0	Filter G3/4 40µm with metal bowl and automatic drain
DF.54 AM10 B	9.1154.00.403.0V	Filter G3/4 40µm with PC bowl, bowl guard and automatic drain
DF.55 HA3	9.1155.00.350.0V	Filter G1 40µm with PC bowl and semi automatic drain
DF.55 M HA3	9.1155.00.352.0V	Filter G1 40µm with metal bowl and semi automatic drain
DF.55 HA3 B	9.1155.00.353.0V	Filter G1 40µm with PC bowl, bowl guard and semi automatic drain
DF.55 AM10	9.1155.00.400.0V	Filter G1 40µm with PC bowl and automatic drain
DF.55 M AM10	9.1155.00.402.0	Filter G1 40µm with metal bowl and automatic drain
DF.55 AM10 B	9.1155.00.403.0V	Filter G1 40µm with PC bowl, bowl guard and automatic drain


Filter

Filter | BG5






flow characteristic



symbol



technical data

- description: sinter filter centrifugal principle
 medium: compressed air, neutral gases
 supply pressure P1 min.: 1,5 bar

- supply pressure P1 max.: 16 bar
 temperature range: -10°C +60°C
 bowl: PC
 drain: HA3

- mounting: vertical
- filter element: 40 µm

accessories

type	part-number	description
DF.56 HA3	9.1156.00.350.0V	Filter G1 1/4 40µm with PC bowl and semi automatic drain
DF.56 M HA3	9.1156.00.352.0V	Filter G1 1/4 40µm with metal bowl and semi automatic drain
DF.56 HA3 B	9.1156.00.353.0V	Filter G1 1/4 40µm with PC bowl, bowl guard and semi automatic drain
DF.56 AM10	9.1156.00.400.0V	Filter G1 1/4 40µm with PC bowl and automatic drain
DF.56 M AM10	9.1156.00.402.0V	Filter G1 1/4 40µm with metal bowl and automatic drain
DF.56 AM10 B	9.1156.00.403.0V	Filter G1 1/4 40µm with PC bowl, bowl guard and automatic drain
DF.57 HA3	9.1157.00.350.0V	Filter G1 1/2 40µm with PC bowl and semi automatic drain
DF.57 M HA3	9.1157.00.352.0V	Filter G1 1/2 40µm with metal bowl and semi automatic drain
DF.57 HA3 B	9.1157.00.353.0V	Filter G1 1/2 40µm with PC bowl, bowl guard and semi automatic drain
DF.57 AM10	9.1157.00.400.0V	Filter G1 1/2 40µm with PC bowl and automatic drain
DF.57 M AM10	9.1157.00.402.0	Filter G1 1/2 40µm with metal bowl and automatic drain
DF.57 AM10 B	9.1157.00.403.0V	Filter G1 1/2 40µm with PC bowl, bowl guard and automatic drain